DRAWING INDEX

SHEET NO TITLE

COVER SHEET
G001 SUMMARY OF PAY ITEMS
A101 ROOF DEMOLITION PLAN
A102 ROOF PLAN
A103 ROOF TAPERED PLAN
A501 ROOF DETAILS
A502 ROOF DETAILS
A503 ROOF DETAILS


CONSTRUCTION PLANS FOR


ROOF REPLACEMENT TULSA PERFORMING ARTS CENTER

110 EAST 2ND STREET TULSA, OKLAHOMA

PROJECT NO. 145380 ACCOUNT NUMBER: 145380 . BUILDINGS - 4053122-541104

CITY OF TULSA OKLAHOMA ENGINEERING SERVICES DEPARTMENT







GENERAL NOTES

- ALL CONSTRUCTION SHALL BE IN STRICT ACCORDANCE WITH CURRENT CITY OF TULSA ORDINANCES, ENGINEERING SERVICES STANDARDS SPECIFICATIONS AND STANDARD DETAILS (CITY OF TULSA ORDINANCE AND CODES AMENDMENTS SUPERCEDE NATIONAL CODES)
- 2. CONTRACTOR SHALL BE RESPONSIBLE FOR DAMAGE TO ALL STRUCTURES, LANDSCAPING, PAVING AND ANY OTHER ITEMS LOCATED WITHIN AND OUTSIDE THE WORK AREA. ANY DAMAGE TO PERMANENT ITEMS INCURRED BY THE CONTRACTOR THROUGH HIS WORK IN THIS CONTRACT SHALL BE REPAIRED TO ORIGINAL CONDITION, BY THE CONTRACTOR AT HIS OWN EXPENSE.
- 3. CONTRACTORS WILL COORDINATE WITH IDENTIFIED MAINTENANCE OPERATIONS PERSONNEL FOR APPLICATION, SHUT OFF AND REMOVAL OF ALL UTILITIES.

PLANS PREPARED BY:

SGA Design Group, P.C. §

Christopher B. Goble, Architect 1437 South Boulder, Suite 550 Tulsa, Oklahoma 74119,3609 p: 918.587.8600 f: 918.587.8601 www.saadesigngroup.com



DATE/STAMP/SIGNATURE



APPROVED BY

Offy ENGINEER

1/1/20 DATE

GENERAL SCOPE OF WORK		UNIT KEY
- REMOVE ROOF SYSTEM, INSULATION, WOOD BLOCKING AND FLASHING DOWN TO STRUCTURAL DECK - UNO.	EA	EACH
 REMOVE ROOF HATCHES, SMOKE VENTS AND SECURELY STORE FOR REINSTALLATION. REMOVE PARAPET CAP FLASHING. 	LF	LINEAR FEET
 REMOVE MISCELLANEOUS EQUIPMENT. INSTALL NEW POLY ISO INSULATION TO ACHIEVE R-VALUE OF R-25 (UNO), NEW 1/4" DENS DECK, NEW FULLY ADHERED 80 MIL TPO MEMBRANE ROOF, ASSOCIATED FLASHING. 	SF	SQUARE FEET
WATERPROOFING PARAPET MEMBRANE AND CAP FLASHING. - REINSTALL EXISTING RTU AND RUN CONDENSATE PIPING.	SQ	SQUARE (100 SQUARE FEET)
- REPLACE LADDER. - INSTALL LADDER SAFETY POST. - MISCELLANEOUS REPAIRS.	WK	WEEK
	ALLO.W	ALLOWANCE

	REPLACEMENT	Project location: 110 East 2nd street, Tulsa, OK Project Number: 145380
ITEM NO.	SPEC NO.	DESCRIPTION
	1 Div One	General Requirements
	2 012100	Owner Allowances
	3 013100	Equipment rehtal (crane)


TEM NO.	SPEC NO.	DESCRIPTION		UNIT	TOTAL
1	Div One	General Requirements	A	EA	1
2	012100	Owner Allowances	В	ALLOW	1
, 3	013100	Equipment rental (crane)	Q	WK	9
4	024119	Demolition of existing roof system	С	EA	. 1
、 5	055100	Installation of new roof access ladders	D	EA	1
6	061053	Misc wood rough capentry	Ε	LF	2,052
7	075423	Installation of new roofing system (including all parapets/flashing	F	ĒΑ	1
. 8	077100	Downspout and collector box	0	EA	. 6
.9	077100	Overflow scuppers	Ĺ	EA	- 4
10	077213	Re-install roof curbs	G	LF	27
11	079200	Replacement of joint sealants	Н	LF	1,000
. 12	099000	Painting	J	SF	1,627
13	221000	Condensate piping	К	LF	40
14	221426	Remove existing roof drains	M	EA	26
15	221426	Install new and replace existing roof drains	N	EA	32
16	260500	Remove and reinstall electrical	, P	LF	150
					


	DURING CERTAIN TIMES OF THE CONSTRUCTION.
Q	PROVID SPECIALITIES EQUIPMENT FOR DEPRIS REMOUNT AND MOVING MOTERIAL & HIGHER ROOPS. MY INCLUDE CRAYE RENTAL
Р	Remove all existing roof top electrical conduit, antenna, security cameras and blocking used for supports. Provide and install weather tight conduit, disconnects, junction boxes, wire, conduit supports and new weather heads for complete- installation of the equipment. Verify that all reinstalled equipment is in good operating condition. Coordinate any disruption of operation of the equipment with operatic Provide all labor, equipment, and materials required to disconnect and reconnect electrical services to all equipment. Restore equipme to operation as quickly as possible.
0	Provide sheet metal overflow scuppers as indicated on the construction documents. Terminate scupper downspouts to spash blocks at the lower roof and provide an 8' walkpad under the splash block and in the downflow direction to the appropriate drain.
N	New drains are added to roof #7. Provide piping under structure to tie in to the existing drain lines at the center of roof #7. Includes all labor, equipment and materials as required for a complete installation.
M	Remove existing roof drains replace with new roof drains as indicated on the drawings and as specified. Make necessary adjustments t install to existing plumbing.
L	Install new overflow scuppers. Core drill existing precast concrete panels as to avoid any panel reinforcing. Make installation water tight accordance with the construction documents.
К	Remove existing and install new condensate piping as indicated on the construction documents. Includes all labor, equipment and materials as required for a complete installation. Support condensate lines as required.
J	Clean and prepare surfaces and substrates for paint systems application. Paint areas as indicated on Drawings. Perform the Work in strict accordance with the Drawings, specifications and manufactures recommendations as required for a complete installation.
Н	Remove all existing joint sealants. Clean and prepare surfaces and substrates for joint sealant application. Seal all masonry/precast panels where cracks or settlement has occurred. Provide all labor, equipment and materials as required for complete preparation and installation of Joint Sealants
G	Existing roof hatches and smoke vents are to be reconditioned to operate like new before they are reinstalled. Provide wood blocking under the curbs to bring the height up to accommodate the additional thickness of the new insulation. Reinstall in the original configuration. Paint as prescribed in the construction documents.
F	Furnish and install new membrane roofing system. Including, but not limited to, single ply membrane, fully-adhered to cover board, and insulation as specified in referenced specification sections. Includes roofing system and components; all roofing specialties, all copings and manufactured roof edge fascia system. Includes all labor, equipment, and materials required for a complete installation of a fully waterproof and warranted membrane roofing system.
Е	Furnish and install materials for all miscellaneous rough carpentry including all wood framing, blocking, nailers and fasteners intended un accordance with Drawings and Specifications.
D	Furnish and install access ladder from high roof to lower roofs on either side. Furnish and install all materials, equipment, labor for complete installation ready for intended use in accordance with Drawings and Specifications.
С	Demolish existing roofing system down to structural deck. Remove roofing/flashing from parapets and other substrates. Remove existin fascia and trim. Remove all wood cants, blocking, and nailiers. Remove all existing fasteners. Removeexisting roof hatches and smoke vents to be stored for re-use. Recycle waste materials where possible. Properly dispose of materials that cannot be recycled in approve landfill. Contractor shall examine existing substrate(s) and adjacent materials for rust, dámage, or other areas of concern.which could prevent successful application of new roofing system. Notify Architect if areas of concern exist.
В	Allowance to be included in the contract amount for additional scope of work to be performed by the Contractor not explicitly defined in contract documents. Funds to be utilized only at the discretion of the Owner and must be agreed upon in written documentation betwee the Owner and Contractor. Any work performed by the Contractor not agreed upon in writing will be at Contractor risk. Any remaining balance will be credited back to the Owner by the Contractor upon final completion of Project.
Α	Division One: General Conditions and miscellaneous direct and indirect Project costs required by the Contract Documents but not liste as a specific Unit Price Pay Item in the Proposal. Includes, but is not limited to: General Conditions covering miscellaneous non-staffic costs directly related to the Project, such as job trailer, mobilization, permit fees (other than Building Permit provided by City of Tulsa), temporary utilities, permanent utility connection fees, barriers, scaffolding, equipment rental, cleaning and dumpsters, etc. Each Unit Price will be deemed to include an amount considered by the Contractor to be adequate to cover Contractor's overhead and profit for each separately identified item.

GENERAL NOTES

- 1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND QUANTITIES.
 2. COORDINATE ANY DISRUPTION OF SERVICES OR OPERATIONS WITH CITY CONSTRUCTION MANAGER.
 3. THE LISTED QUANTITIES ARE ONLY AN ESTIMATION, IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL EXISTING CONDITIONS PRIOR TO THE SUBMISSION OF HIS BID AND TO THE COMMENCEMENT OF ANY WORK, NO ADDITIONAL COMPENSATION WILL BE PAID DUE TO THE CONTRACTOR'S FAILURE TO ACQUAINT HIMSELF WITH EXISTING SITE CONDITIONS WHICH INCLUDE, BUT ARE NOT LIMITED TO QUANTITY AND EXTENT OF SURFACES AND MATERIALS OR UTILITIES.

SYMBOLS LEGEND






TULSA PERFORMING ARTS CENTER

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. &

K	REVISION	BY	DATE	PLAN	DRAWN	edm	6/2020	APPROVED:
				SCALE:	DESIGNED	edm	6/2020	
				1 =	SURVEY	N/A		
			,	PROFILE	PROJ. MGR.	M	4/20	
				SCALE: 1" =	LEAD ENGR.	mes	6/2020	
				HORIZONTAL:	FIELD MGR.	TOW	6/20	11
				1" = VERTICAL:	RECOMMEND		6.20	
				1" =	DESIGN MAN	IAGER		CITY ENGIN
				FILE:	DRAWIN	IG:		DATE: 6.2
				ATLAS PAGE	NO:			SHEET :
				SHEET NAME	SUMN	1AR	Y OF	SHEET NO.

PAY ITEMS G001



GENERAL NOTES

- REMOVE EXISTING ROOF SYSTEM, INSULATION, WOOD BLOCKING AND FLASHING DOWN TO STRUCTURAL DECK, UNO.
- REMOVE EXISTING RÓOFTOP EQUIPMENT. SECURELY STORE UNITS TO BE RE-INSTALLED. COORDINATE REMOVAL/ REINSTALLATION TIMING WITH OWNER.
- COORDINATE RE-ROOFING OPERATIONS TO PREVENT WATER INFILTRATION INTO BUILDING DURING CONSTRUCTION. CONTRACTOR WILL BE RESPONSIBLE FOR ANY WATER DAMAGES TO CONTENTS OF THE BUILDING DURING RE-ROOF OPERATIONS.
- IF EXISTING STRUCTURAL DECK IS SHOWING SIGNS OF RUST, DAMAGE OR FAILURE, PLEASE NOTIFY ARCHITECT PRIOR TO PROCEEDING.
- RELOCATE ELECTRICAL CABLING AS NECESSARY WHILE MAINTAINING LIGHTS AND CAMERA OPERATION. COORDINATE WITH OPERATIONS.

KEYNOTES NOTES

- 1. DEMOLISH BOTH EXISTING GRAVEL BALLASTED BUILT UP AND MODIFIED ROOFS IN THEIR ENTIRETY. DEMOLISH ALL RELATED BASE FLASHING, FLASHING, COUNTER FLASHING AND APPURTENANCES. PATCH AND REPAIR REMAINING SURFACES FOR ROOF INSTALLATION. TYP.
 2. REMOVE EXISTING ROOF HATCH AND CURB SAVE TO BE REPAIRED IF REQUIRED AND REINSTALLED.
 3. REMOVE EXISTING ROOF DRAINS. REPAIR ANY DAMAGED DECKING AND PREP FOR NEW DRAINS.
 4. REMOVE EXISTING CONDENSATE LINES. PROVIDE TEMPORARY LINE FOR RTU CONDENSATE.
 5. EXISTING RTU TO REMAIN.
 6. REMOVE EXISTING ROOF LADDER TO BE REPLACED.
 8. SMOKE VENTS AND CURBS TO BE REMOVED. THE SMOKE VENTS ARE TO BE REPAIRED IF REQUIRED AND REINSTALLED.
 9. FIRE CONNECTION TO REMAIN. REMOVE RUST AND EXISTING PAINT. VERIEY PROPER OPERATION, 10. SECURITY CAMERA TO BE REMOVED AND SAVED FOR RE—INSTALLATION.
 10. SECURITY CAMERA TO BE REMOVED AND SAVED FOR RE—INSTALLATION.

- 10. SECURITY CAMERA TO BE REMOVED AND SAVED FOR RE—INSTALLATION
 11. EXISTING ROOF VENT TO REMAIN.
 12. ELECTRICAL CONDUIT TO BE TEMPORARILY RE—ROUTED
 13. REMOVE EXISTING WALL FLASHING.
 14. REMOVE EXISTING PARAPET FLASHING.
 15. REMOVE EXISTING GRAVEL STOP AND FASCIA.



ROOF REPLACEMENT TULSA PERFORMING ARTS CENTER

PROJECT NO.:145380

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. &

	and the second	2		
мĸ	REVISION	BY DATE	PLAN DRAWN edm 6/2020	APPROVED:
,			SCALE: DESIGNED edm 6/2020]
۲.			1" = SÚRVEY N/A	
			PROFILE PROJ. MGR. M 6/20	
			SCALE: 1" = LEAD ENGR. 12-24	<u>.</u>
			HORIZONTAL: FIELD MGR. JUL 6/20	1/ 5
	.,		1" = RECOMMENDED: VERTICAL: HAS 6.20	Ida
			1" = DESIGN, MANAGER	CITY ENGINE
			FILE: DRAWING:	DATE: 6 . 1
			17 10 D105 NO	OUEST 7

ATLAS PAGE NO

PLAN

SHEET NAME:


SHEET 3 OF 8 SHEETS SHEET NO. **ROOF DEMOLITION**

A101

12b.20

ROOF DEMOLITION PLAN





ROOF PLAN



- COORDINATE RE—ROOFING OPERATIONS TO PREVENT WATER INFILTRATION INTO BUILDING DURING CONSTRUCTION. CONTRACTOR WILL BE RESPONSIBLE FOR ANY WATER DAMAGES TO CONTENTS OF THE BUILDING DURING RE—ROOF OPERATIONS.
- COORDINATE ANY MECHANICAL FASTENERS WITH ELECTRICAL CONDUIT THAT MAY BE INSTALLED. CONTRACTOR WILL BE RESPONSIBLE TO REPAIR ANY EXISTING ELECTRICAL DAMAGED DURING REROOFING OPERATIONS.
- STAGGER JOINTS BETWEEN LAYERS OF POLYISO INSULATION. NO JOINTS BETWEEN LAYERS SHOULD ALIGN.
- REMOVE ALL GRAVEL FROM ROOF SURFACE, DO NOT INSTALL MEMBRANE OVER ANY LOOSE GRAVEL ON ROOF SURFACE.

KEYNOTES NOTES

- INSTALL FULLY ADHERED 80 MIL TPO ROOFING SYSTEM ON COVER BOARD OVER TAPERED INSULATION AND BASE OF R-25 POLYYSO INSULATION. PROVIDE MANUFACTURES FLASHINGS AND ACCESSORIES FOR COMPLETE INSTALLATION. INSTALL MINIMUM 3" BASE LAYER OF POLYISO UNDER TAPERED AREAS.
- COMPLETE INSTALLATION. INSTALL MINIMUM 3" BASE LAYER OF POLYISO UNDER TAPERED AREAS.

 A. INSTALL 1 3" POLYISO INSULATION ON ROOF #6 AS NOT TO INCREASE THE ORIGINAL ELEVATION OF THE ROOF MEMBRANE.

 REPAIR ROOF HATCHES AS REQUIRED FOR PROPER OPERATION. REPAINT HATCHES P2. RAISE 3" W/NEW 2X NAILERS SECURED TO STRUCTURE. EACH ROOF HATCH LADDER TO BE ADJUSTED AT THE REQUIRED HEIGHT AND INSTALL NEW SAFETY POST PER DETAIL 4/A502. REPLACE EXISTING DRAINS WITH NEW DRAINS PER 5/A501. USE EXISTING DRAIN LINES.

 ROUTE CONDENSATE DRAINS DIRECTLY DOWN OUT OF THE RTU AND RUN IN PVC PIPE THROUGH STRUCTURE TO NEAREST INTERIOR DRAIN.

 EXISTING RTU TO REMAIN. PROVIDE COUNTER FLASHING FOR NEW ROOF TO CREATE A WATER TIGHT SEAL. REINSTALL ANTENNA UNITS. PROVIDE A BOOTED WEATHER HEAD FOR CABLING ROUTED BELOW ROOF.

 INSTALL NEW ROOF LADDER PER OSHA REQUIREMENTS. REPAIR SMOKE VENTS IF REQUIRED AND RE—INSTALL IN ORIGINAL LOCATIONS WITH AN ADDED 3" NAILERS TO RAISE THE UNITS UP 3".

 3. RE—INSTALL IN ORIGINAL LOCATIONS WITH AN ADDED 3" NAILERS TO RAISE THE UNITS UP 3".

 3. RE—INSTALL SECURITY CAMERAS PER OPERATIONS DIRECTIONS. REF—PAINT P3.

 3. RE—INSTALL SECURITY CAMERAS PER OPERATIONS DIRECTIONS. INSTALL BOOK PAINT P3.

 3. RE—INSTALL SECURITY CAMERAS PER OPERATIONS DIRECTIONS. INSTALL BOOK PINSTALL BOOK PAINT P3.

 4. RESISTING PLUMBING VENTS TO BE BOOTED WITH NEW ROOFING PREMERAS PER OPERATIONS DIRECTIONS INSTALL BOOK PINSTALL ADDITED WEATHER HEAD FOR CABLING PEMBRANE WISSTALL BOOK PINSTALL ADDITED WEATHER HEAD FOR CABLING PEMBRANE WISSTALL BOOK PINSTALL ADDITED WE WENTS TO BE BOOTED WITH NEW ROOFING PEMBRANE WISSTALL BOOK PINSTALL ADDITED WEATHER HEAD FOR CABLING PEMBRANE WISSTALL BOOK PINSTALL ADDITED WE PEMBRANE PINSTALL ADDITED WE PEMBRANE PINSTALL ADDITED WE PEMBRANE PINSTALL BOOK PEMBRANE PINSTALL BOOK PINSTALL BOOK PINSTALL BOOK PEMBRANE PINSTALL BOOK PINSTALL ADDITED WITH PAINSTALL BOOK PINSTALL BOOK PINS

- CABLING PENETRATIONS. REFER 2/ASO3

 12. EXISTING PLUMBING VENTS TO BE BOOTED WITH NEW ROOFING MEMBRANE INSTALLATION. REFER 4/ASO1

 13. ALL ELECTRICAL CONDUCTORS ARE TO BE ROUTED BELOW THE ROOF.

 14. NEW WALL FLASHING TO BE INSTALLED AT PRECAST PANELS. REFER ROOFING DETAILS.

 15. INSTALL PREFINISHED METAL FASCIA

 16. WALK PADS WELDED TO NEW TPO ROOF. DO NOT INSTALL OVER SEAMS OR CORNER FLASHING.

 17. 8X8 COLLECTOR INTO 4/4 DOWNSPOUT TO DISCHARGE ONTO CONCRETE SPLASH BLOCK SET ON 30"x96" WALK PAD. REFER DETAIL 7&9/ASO2.

 18. INSTALL 8"JOSAM(OR EQUAL) DOWNSPOUT NOZZLE 8. INSTALL 8"JOSAM(OR EQUAL) DOWNSPOUT NOZZLE
- 8. INSTALL 8 JOSAMOR EQUAL) DOWNSPOUT NOZZLE W/FLANCE 4" ABOVE ASSOCIATED PRIMARY DRAIN. REFER 3/A503.

 9. INSTALL NEW ROOF DRAINS PER DRAIN MANUF. RECOMMENDATIONS. PIPE DRAIN LINES INTO EXISTING ROOF DRAIN SYSTEM. REFER 5/A501



TULSA PERFORMING ARTS CENTER

PROJECT NO.:145380

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. S

	 4	
		Ì
	1.	
		

RECOMMEND VERTICAL: DESIGN MANAGER DRAWING: ATLAS PAGE NO:

HORIZONTA

SHEET 4 OF 8 SHEETS SHEET NAME: SHEET NO.

ROOF PLAN

DESIGNED edm 6/2020


PROJ. MGR. My 4/20 LEAD ENGR. MAN 6/2020 FIELD MGR. JEW 6/20

DRAWN

SURVEY

A102

NOTE: TAPER PATTERN IS DIAGRAMMATIC. GC TO SUBMIT TAPER PLAN FOR OWNER APPROVAL





TULSA PERFORMING ARTS CENTER

PROJECT NO.:145380


CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. Christopher B. Goble, Architect 1437 South Boulder, Sulfus 50 Tulso, Oklahomar 74119,1509 19 18,587,8601 19 18,587,8601 19 19,587,8601 19 19,587,8601

					PLAN	V	#1515		A100
				RC	OF TAP	PER	ED		A103
				SHEET NAME		3		SHEET NO	o.
				ATLAS PAGE	NO:			SHEET	5 OF 8 SHEETS
				FILE:	DRAWIN	G:		DATE: 6.	26.10
				1" =	DESIGN MAN			CITY ENG	NEER)
				1" = VERTICAL:	RECOMMEND	ED: HAS	6.20	Mille	
				HORIZONTAL:		· •	6/20	1/10	00_
				1" =	LEAD ENGR.				
				PROFILE -SCALE:	PROJ. MGR.	W	6/20		
1				1" =	SURVEY	N/A			
		1		SCALE:	DESIGNED	edm	6/2020		
MK .	REVISION	BY	DAJE	PLAN.	DRAWN	edm	6/2020	APPROVE	D: 1

1 TAPERED INSULATION






2'-6"x2'-6" WALKWAY PADS SPACED 3" APART LOCATED ON ALL SIDES OF RTU AND ADJACENT TO ROOF HATCH

WALK

ROOF HATCH




RTU


PVC CONDENSATE PIPE


8 PIPING SUPPORT PLAN

7 PAD LAYOUT




5 ROOF DRAIN DETAIL







9 PENETRATION
1 1/2"=1'-0"



6 PENETRATION
1 1/2"=1'-0"



4 PENETRATION 1 1/2"=1"-0"





TULSA PERFORMING ARTS CENTER


PROJECT NO.:145380

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT


SGA Design Group, P.C. S.

Christopher B. Gobie, Architect 1437 South Boulder, Suite 550 Tulso, Oklahomo 74119.3609 p: 918.587.8600 f: 918.587.860 www.sgodesigngroup.com


MK	REVISION	BY	DATE	PLAN_	DRAWN	edm (6/2020	APPROVE	D:		
				SCALE:	DESIGNED	edm	6/2020				
				1" =	SURVEY	N/A					
				PROFILE SCALE:	PROJ. MGR.	M	6/20				
				1" =	LEAD ENGR	ma	6/2000				
				HORIZONTAL:	FIELD MGR.	Zu	6/20	1/5	\mathcal{O}	,	
				1" = VERTICAL:	RECOMMEND	HAS	6.20	Mille			
				1" =	DESIGN MAN	NAGER			INFER)	
				FILE:	DRAWN	NG:		DATE:	26.	10	
				ATLAS PAGE	E NO:			SHEET		8 SHE	ETS
				SHEET NAMI	E:			SHEET N	0.		
		-		ROOF	DETAIL	_S				A50	1




SCUPPER ISOMETRIC AT ROOF CURB




DOWNSPOUT SPLASH






8 FLASHING DETAIL




PARAPET CAP FLASHING

6) PARAPET CAP FLASHING




2 COVER BOARD ATTACHEMENT





1) FLASHING MEMBRANE





PROJECT NO.:145380


B. GOBLE


CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. &

stopher B. Goble, Architect 7 South Boulder, Suite 550 fulso, Oklohomo 74119,3609 p. 918,587,8600 fr. 918,587,8601 www.sgodesigngroup.com

МK	REVISION	BY	DATE	PLAN_	DRAWN	edm	6/2020	APPROVED):
				SCALE:	DESIGNED	edm	6/2020		
] =	SURVEY	N/A			
				PROFILE SCALE:	PROJ. MGR.	W	6/10		
				1" =	LEAD ENGR.	mid	6/2020		_
				HORIZONTAL:	FIELD MGR.	ZZW	6/20	1/1	()
				1" = VERTICAL:	RECOMMEND	F\$45	6.20	1600	X
				1" =	DESIGN MAN			CITY ENGI	NEER ()
				FILE:	DRAWN	IG:		DATE: 6.	26.20
				ATLAS PAGE	NO:			SHEET	7 OF 8 SHEETS
				SHÉET NAME	3:			SHEET NO).
		-		ROOF	DETAIL	.S			A502





1) PARAPET CAP FLASHING



TULSA PERFORMING ARTS CENTER

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

SGA Design Group, P.C. S. Christopher B. Goble, Architect 1437 South Boulder, Suite 550 Tulse, Oklahomo 7119.3509 p: 915.987.8800 fr. 916.967.8801

MK	-	REVISION	BY	DATE	PLAN	DRAWN	edm	6/2020	APPROVED):
					SCALE:	DESIGNED	edm	6/2020		
					1" =	SURVEY	N/A			
					PROFILE SCALE:		W	6/10		
					1" =	LEAD ENGR.	mad	6/2020	_	
					HORIZONTAL:		Zu	6/2	1/6) /
			1	3	1" = VERTICAL:	RECOMMEND	Has	6.20	(held)	
					1" =	DESIGN MAN	AGER		CITY ZNG	₩EB)
					FILE:	DRAWIN	G:		DATE:	26.20
				,	ATLAS PAGE	NO:			SHEET	8 OF 8 SHEETS
					SHEET NAME	:			SHEÈT NO).
					ROOF	DETAIL	S			A503