

**SECTION 10 1101  
VISUAL DISPLAY BOARDS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Markerboards and Tackboards.

**1.02 RELATED REQUIREMENTS**

- A. Section 06 1000 - Rough Carpentry: Blocking and supports.
- B. Section 09 2216 - Non-Structural Metal Framing: Concealed supports in metal stud walls.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide manufacturer's data on markerboard, tackboard, trim, and accessories.
- C. Manufacturer's printed installation instructions.
- D. Maintenance Data: Include data on regular cleaning, stain removal , and \_\_\_\_\_.

**1.04 QUALITY ASSURANCE**

- A. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.

**1.05 WARRANTY**

- A. See Section 01 7800 - Closeout Submittals, for additional warranty requirements.
- B. Provide five year warranty for chalkboard and markerboard to include warranty against discoloration due to cleaning, crazing or cracking, and staining.

**PART 2 PRODUCTS**

**2.01 MANUFACTURERS**

- A. Visual Display Boards:
  - 1. Claridge Products and Equipment, Inc ; \_\_\_\_: [www.claridgeproducts.com](http://www.claridgeproducts.com).
  - 2. MooreCo, Inc ; \_\_\_\_: [www.moorecoinc.com](http://www.moorecoinc.com).
  - 3. Polyvision Corporation (Nelson Adams) ; \_\_\_\_: [www.polyvision.com](http://www.polyvision.com).
  - 4. Substitutions: See Section 01 6000 - Product Requirements.

**2.02 VISUAL DISPLAY BOARDS**

- A. Markerboards: Basis of Design: Claridge LCS2044R LCS Magnetic Porcelain Enamel with box tray.
  - 1. Color: 92 LCSII White.
  - 2. Height: 48 inches (1220 mm).
  - 3. Length: 8 feet (2440 mm) , in one piece.
  - 4. Frame: Extruded aluminum , with concealed fasteners.
  - 5. Frame Finish: Anodized, natural.
- B. Tackboards: Fine-grained, homogeneous natural cork.
  - 1. Cork Thickness: 1/8 inch (3 mm).
  - 2. Height: 48 inches (1220 mm).
  - 3. Length: 48 inches (1220 mm) , in one piece.
  - 4. Frame: Extruded aluminum , with concealed fasteners.
  - 5. Frame Profile: As indicated on drawings
  - 6. Frame Finish: Anodized, natural.

**2.03 ACCESSORIES**

- A. Temporary Protective Cover: Sheet polyethylene, 8 mil (0.2 mm) thick.
- B. Chalk Tray: Aluminum , manufacturer's standard profile , one piece full length of chalkboard , molded ends, concealed fasteners, same finish as frame.

- C. Mounting Brackets: Concealed.

### **PART 3 EXECUTION**

#### **3.01 EXAMINATION**

- A. Verify that field measurements are as indicated.
- B. Verify that internal wall blocking is ready to receive work and positioning dimensions are as indicated on shop drawings.

#### **3.02 INSTALLATION**

- A. Install boards in accordance with manufacturer's instructions.
- B. Secure units level and plumb.

#### **3.03 CLEANING**

- A. Clean board surfaces in accordance with manufacturer's instructions.
- B. Cover with protective cover, taped to frame.
- C. Remove temporary protective cover at Date of Substantial Completion.

**END OF SECTION 10 1101**